# Re-Post: Cron

Note: This is taken from my previous blog - Published on: Jul 11, 2011 @ 10:35

Sounds very computer-ish isn't it? Well, it is... it's actually a scheduling table, something that computer system admins are very familiar with. It's nothing fancy, I could have written this in my wiki, which is what I usually would have done. But, since it's been quite a while since I last write something in this blog, I just feel like putting the info here. I know I'm going to regret this and spend more time transferring this to my wiki later... but I'll do it anyways :-p

A task/job is made of 1 line with 6 items - 5 items/numbers represent time, and the last one is the job/task to be executed. Check it out...

```
*    *    *    *    *    job/task_to_be_executed
|    |    |    |    |
|    |    |    |    |
|    |    |    |    |
|    |    |    |    |____ weekday (0 - 7) 0/7 => Sunday
|    |    |    |_____ month (1 - 12)
|    |    |_____ day (1 - 31)
|    |_____ hour (0 - 23)
|_____ minute (0 - 59)
```

I got the above 'figure' from wikipedia (with minor personal adjustments). To view your current cron jobs, type

```
crontab -l
```

So, how do we 'install' a new job? Type

```
crontab -e
```

which will open your default terminal editor (e.g. vi) and enter a task in the given format, then save. Voila!

Update20220307 So, after more than 10 years, I finally manged to transfer this to my wiki's mini-blog. Yay! 😎 Here are some additional info..

Some examples:

- To run binary `tool` every hour:

  ```
  0 * * * * /path/to/tool <args>...
  ```

Special cases:

- To run binary `tool` every 5 minutes:

```
*/5 * * * * /path/to/tool <args>...
```

- To run binary `tool` on reboot/startup:

```
@reboot /path/to/tool <args>...
```

[computing](), [linux]()

From:
http://azman.unimap.edu.my/dokuwiki/ - **Azman @UniMAP**

Permanent link:
http://azman.unimap.edu.my/dokuwiki/doku.php?id=blog:2022:0307_re-post_cron

Last update: **2023/08/29 10:43**