

Slackware in chroot

20110621 I want to have a 32-bit system running in chroot environment on my Slackware64. I've used such system on Debian using schroot...

20110906 I managed to do this as published [here](#)...

20120518 Minor change to the fstab entry for dev, which needs an rbind option so that the pty inside can be valid! Discussed [here](#).

20120524 This is now part of my slackstuff collection (now known as [my1shell](#))... in form of a script called slackroot.

20121031 The path to the chroot installation MUST ALL BE owned by root - or else, users will get a Write failed: Broken pipe error.

TODO A how-to on creating 32-bit chroot on 64-bit Slackware using *slackroot* script.

[slack_chroot32.txt](#)

```
- on my pure slack64 (maintained using getslack/getslackpack)
$ ARCH=i686 getslack

- create root filesystem using 32-bit packages
# slackroot /opt/chroot32 --arch x86 --desk -x

- copy user/group info from 64-bit system to chroot32
  = will maintain its own login info!
# preproot --init /opt/chroot32

- mount bind 'system' paths
# preproot /opt/chroot32

- ssh into system to use 32-bit chroot
# ssh user@127.0.0.1

- unmount bind 'system' paths
# preproot --done /opt/chroot32
```

From:

<http://azman.unimap.edu.my/dokuwiki/> - Azman @UniMAP

Permanent link:

http://azman.unimap.edu.my/dokuwiki/doku.php?id=linux:slack_2chroot

Last update: **2025/01/12 09:59**

