

Slackware System

Useful system level notes.

Listing Packages

Simply list files in /var/log/packages (path is actually a link to /var/lib/pkgtools/packages/).

```
# ls -l /var/log/packages/
```

List full package name (with version) only

```
# for that in $(ls /var/log/packages/) ; do echo $that ; done | sort
```

Find installed packages that are not in Slackware tree

```
slackfull=slackware64-15.0 ; slacktree=/home/share/slackware/$slackfull ;  
for pkg in $(ls /var/log/packages/) ; do  
    pkgf=$(find $slacktree/ -name "${pkg}.txz") ;  
    [ -f "$pkgf" ] && continue ;  
    echo "** Package '$pkg' is alien!" ;  
done
```

This can also be done using slackview script (in my1shell repo)

```
# slackview find --alien
```

View information on specific package

```
# slackview find [pkg_name]
```

To list currently installed packages (to be used in my1live)

- get all installed packages

```
# slackview file --name pkgs.txt --installed --insert
```

- sort based on software sets

```
# slackview file --name pkgs.txt --sort
```

- remove those already selected for my1live

```
slackview file --name pkgs.txt --dups curr.list
```

- rename pkgs.txt to my1live list (e.g. XXmore.list)

Building Custom Kernel

- run shell script ([getlinux](#))
- select version, download source
- extract at /usr/src/ (e.g. linux-4.4.199)
- copy a config from /boot

```
# cp /boot/config-generic? > .config
```

- use that config

```
# make oldconfig
```

- configure build

```
# make menuconfig
```

- build the kernel

```
# make -j4 bzImage
```

- build/install modules

```
# make -j4 modules && make modules_install
```

- modules_install requires root, obviously!

- copy (as root) kernel

```
cp arch/x86/boot/bzImage /boot/vmlinuz-generic-4.14.12  
cp System.map /boot/System.map-generic-4.14.12  
cp .config /boot/config-generic-4.14.12
```

- generate initrd if using generic

```
mkinitrd -c -k 4.14.12 -f ext4 -r /dev/sda3 -m ext4 -u -o  
/boot/initrd.gz
```

- a useful initrd generator script IS available
- run /usr/share/mkinitrd/mkinitrd_command_generator.sh
- then run the generated/recommended command
- checkout the -P option if required

From:

<http://azman.unimap.edu.my/dokuwiki/> - Azman @UniMAP

Permanent link:

http://azman.unimap.edu.my/dokuwiki/doku.php?id=linux:slack_4system&rev=1736650720

Last update: 2025/01/12 10:58

